




AUTOMATIC TRIMMER MACHINE



DETALLES



TECHNICAL CHARACTERISTICS

• <u>Disc diameter (max./min.)</u>	200-500mm
• <u>Disc thickness (min./max.)</u>	1.5-3.5mm

Cutting capacity

• <u>Max. cutting height</u>	170mm (500mm disc)
• <u>Max. cutting length</u>	Depending on order
• <u>Feeder chains</u>	$\frac{3}{4}$ " – 1"

Rotation speed cutting discs

• <u>200mm disc</u>	4.600rpm
• <u>500mm disc</u>	3.500rpm
• <u>Numero de carros portadiscos</u>	Optional
• <u>Cutting moving forward speed</u>	5-20 rpm
• <u>Cutting motors</u>	3 C.V. – 7.5C.V.
• <u>Cutting moving forward motor</u>	1.5C.V.
• <u>Entrance motor rollers</u>	1C.V.
• <u>Movement of the motorised cart</u>	0.5C.V.
• <u>Opening of the discs protections</u>	Hydraulic

Optional

• <u>Automatic load</u>	Feeder loader
• <u>Belt for the waste extraction.</u>	

MAIMBAR XXI, S.L.

Parque Empresarial de Pazos, parcela 75 15900 Padrón (A Coruña - España)
Teléfono: +34 986 559 494 / Fax: +34 986 559 726 www.maimbar.es